102 00

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)							
(51) International Patent Classification ⁶ :		(11) International Publication Number: WO 98/00602					
D21C 9/14	A1	(43) International Publication Date: 8 January 1998 (08.01.98)					
(21) International Application Number: PCT/SE (22) International Filing Date: 16 June 1997 (European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB,						
(30) Priority Data: 9602602-6 28 June 1996 (28.06.96)	s	Published With international search report.					
(71) Applicant (for all designated States except US): SUNI BRATOR INDUSTRIES AB [SE/SE]; S-851 94 S (SE).							
(72) Inventors; and (75) Inventors/Applicants (for US only): BOMAN, Rolf Idrottsgatan 17, S-856 43 Sundsvall (SE). BOK Monica [SE/SE]; Bjärme 3251, S-860 25 Kovis GERMGÄRD, Ulf [SE/SE]; Mastvägen 5, S-865 (SE). MELLANDER, Pia [SE/SE]; Flottiljvägen 32 Alnö (SE). NORDÉN, Solveig [SE/SE]; O 14, S-862 41 Njurunda (SE). SUNDIN, Matts Skonertvägen 14, S-865 32 Alnö (SE).	M, 3). no 655						
(74) Agent: IVENSEN HASSELROT, Eva; L.A. Groth & P.O. Box 6107, S-102 32 Stockholm (SE).	Co. K.	в.					
(54) Title: PRESSURIZED CHLORINE DIOXIDE BLEACHING WITH RECOVERY OF CHLORINE DIOXIDE							
(57) Abstract	(57) Abstract						
The present invention relates to a multi-stage paper pulp bleaching process in which at least one of the bleaching stages is carried out in a reactor with chlorine dioxide at a pulp concentration of 8-40 %. The pulp is bleached with chlorine dioxide in a pressurized vessel at an overpressure of 0.1-10 bars and at a temperature of between 90-110 °C and for a reaction time of 1-90 minutes. The pressure of the pulp is lowered in a downstream tower in a manner such as to also lower the temperature of the pulp and enable residues of chlorine dioxide to be extracted in gas phase.							

incetink (10m

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albenia	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Pinland	LT	Lithosoia	SK	Slovakia
AT	Austria	FR	Prance	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	15	Iceland	MW	Malawi	US	United States of Americ
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbahwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
СМ	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Batonia	LR	Liberia	SG	Singapore		

WO 98/00602 PCT/SE97/01060

PRESSURIZED CHLORINE DIOXIDE BLEACHING WITH RECOVERY OF CHLORINE DIOXIDE

The present invention relates to a method of bleaching paper pulp with chlorine dioxide in a plurality of stages of which at least one stage is a chlorine dioxide stage.

5

10

15

20

25

30

Modern paper pulp bleaching methods are based on the use of chlorine dioxide (D) as the main bleaching chemical. The bleaching methods often comprise several stages, and the chlorine dioxide bleaching effect is enhanced by also including an oxygen gas stage (O) and/or a hydrogen peroxide stage (P) in the bleaching sequence, such as sequences of the type OP(EPO)DD, where (E) stands for extraction. The pulp is bleached to a high degree of purity by these bleaching methods in a manner which is gentle on the pulp. The load on the environment is also low, since the concentrations of, e.g., AOX, chlorinated phenols, chlorinated dioxins, etc., have been limited by said methods.

Because it has been possible to lower the kappa number as a result of improved pulp digestion and oxygen-gas delignification technology, the need for bleaching chemicals has diminished. In spite of this, the majority of bleaching sequences still require from four to five bleaching stages, due to the fact that the terminating bleaching process is carried out under conditions that cause the reaction mechanisms to take place slowly and ineffectively. In traditional bleaching departments, the pulp is bleached in from five to six bleaching stages in accordance with the aforesaid type of sequence, despite the bleaching requirement being from two to four times greater than in the most modern of present-day pulp mills.

Known chlorine dioxide bleaching processes are comprised of sequences in which the chlorine dioxide stages are carried out at pulp concentrations of about 10-15%. When bleaching is carried

5

10

15

20

25

30

out in a pre-bleaching stage, the temperature is between $20-60^{\circ}$ C at pH 2-3 over a reaction time of 0.5-1 hour. When bleaching is carried out in a final bleaching stage, the temperature is higher, about $50-80^{\circ}$ C, at pH 4-5, although the reaction time is longer, from 2-4 hours.

Bleaching at higher temperatures in order to shorten the reaction time cannot be readily effected, however, on a full scale. It is necessary to carry out the bleaching process in a pressurized reactor instead of in a conventional bleaching tower. When the pressure is dropped, chlorine dioxide gas residues that are harmful to the health are given off. Pulp that contains residual chlorine/residual chlorides cannot be readily passed to a subsequent wash without being cooled, since the wash environment would otherwise become much too corrosive.

The object of the present invention is to solve the aforesaid problems so that the desired bleaching result can be achieved at lower costs.

The characteristic features of the invention will be apparent from the following Claims.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates preferably to the bleaching of paper pulp with chlorine dioxide. The pulp is bleached in several stages, of which at least one stage is a chlorine dioxide stage. The pulp shall have a concentration of 8-40%, preferably 10-15%. The chlorine dioxide bleaching process is carried out in a pressurized reactor at an overpressure of 0.1-10 bars at a temperature of 90-110°C and with a reaction time of 1-90 minutes, preferably 15-30 minutes. Subsequent to treatment with chlorine dioxide, the pulp is transferred to a downstream tower in which

the pressure is lowered, wherein the temperature of the pulp also falls and residues of gaseous chlorine dioxide are released, these residues later being removed with cold water. The water containing chlorine dioxide is recycled to the reactor, where it is charged to the chlorine dioxide stage together with dilution water and additional chlorine dioxide.

<02

The pulp from which gaseous chlorine dioxide has been removed is cooled further by delivering SO_2 -containing water to the bottom of the downstream tower on the suction side of the pump. The pulp is cooled to a temperature that shall not exceed 80°C, whereafter the pulp is pumped to a downstream washing stage. The addition of the SO_2 -containing water enables further residual chlorine in the pulp to be eliminated.

15

The invention will be described hereinafter with reference to an exemplifying embodiment thereof.

20

The pulp to be bleached is paper pulp, for instance sulphite pulp or sulphate pulp.

Example

25

Sulphate pulp/sulphite pulp having a pulp concentration of between 10-15% was treated with chlorine dioxide in a pressurized reactor. The pulp was treated for 15-30 min. at a temperature of about 90-110°C. After treatment with chlorine dioxide, the pulp was transported to a downstream tower in which the temperature was lowered and chlorine dioxide residues were extracted in gas phase, whereafter the pulp was cooled to 80°C by adding SO₂-containing water to eliminate residual chlorine in the pulp.

30

Bleaching can be effected more quickly and more effectively, by bleaching with chlorine dioxide at a higher temperature. The

WO 98/00602 PCT/SE97/01060

4

shorter reaction time in the pressurized vessel enabled the bleaching equipment to be reduced, thereby enabling the costs entailed by ground area and building volume to be also reduced. This represents a considerable reduction in the cost of bleaching paper pulp.

5

10

Other advantages afforded by the inventive method include the recirculation of chlorine dioxide, which enables the burden of chlorine-containing compounds on the environment to be minimized or completely eliminated.

5

10

15

20

25

CLAIMS

- which at least one of the bleaching stages is carried out in a pressurized vessel with chlorine dioxide at a temperature of between 90-110°C and at an overpressure of 0.1-10 bars during a reaction time of 1-90 minutes and at a pulp concentration of 8-40%, preferably 10-15%, characterized by lowering the pressure of the pulp in a downstream tower in a manner such as to also lower the temperature of the pulp and enable chlorine dioxide residues to be extracted in a gas phase, extracting chlorine dioxide from the gas phase with the aid of cold water, and recycling the chlorine-dioxide containing water from the extraction of chlorine dioxide to the reactor together with dilution water, which is charged to the chlorine dioxide stage.
- 2. A method according to Claim 1, characterized in that the reaction time of the chlorine dioxide bleaching process is 15-30 minutes.
- 3. A method according to Claim 1 or 2, characterized by further cooling the pulp with SO_2 -containing water charged to the bottom of the downstream tower, and eliminating residual chlorine present in the pulp.
- 4. A method according to any one of Claims 1-3, characterized by colloing the SO_2 -containing water before charging the water to the pulp.
- 30 5. A method according to any one of Claims 1-4, characterized in that the pulp that is pumped to the following washing stage has a temperature of ≤ 80°C.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/SE 97/01060

A CTAC	SIEICATION OF SUBJECT MATTER					
	A. CLASSIFICATION OF SUBJECT MATTER					
IPC6: I	IPC6: D21C 9/14 According to International Patent Classification (IPC) or to both national classification and IPC					
B. FIELD	B. FIELDS SEARCHED					
Minimum d	Minimum documentation searched (classification system followed by classification symbols)					
IPC6: [
	ion searched other than minimum documentation to the	extent that such documents are included in	the fields searched			
	FI,NO classes as above					
Electronic d	ata base consulted during the international search (name	of data base and, where practicable, search	terms used)			
C. DOCU	MENTS CONSIDERED TO BE RELEVANT					
Category*	Citation of document, with indication, where ap	propriate, of the relevant passages	Relevant to claim No.			
A	SE 9303037-7 A (SUNDS DEFIBRATOR	R INDUSTRIES AB)	1-5			
	17 March 1995 (17.03.95)					
		·				
A	US 2706673 A (E.R.BURLING ET AL) (19.04.55)	1-5				
						
Further documents are listed in the continuation of Box C.						
-	categories of cited documents: ant defining the general state of the art which is not considered	"T" later document published after the into date and not in conflict with the applie the principle or theory underlying the	cation but cited to understand			
to be of	particular relevance ocument but published on or after the international filing date	"X" document of particular relevance: the	claimed invention cannot be			
cited to	ent which may throw doubts on priority claim(s) or which is establish the publication date of another citation or other	considered movel or cannot be considered step when the document is taken alone	1			
-	reason (as specified) ant referring to an oral disclosure, use, exhibition or other	"Y" document of particular relevance: the considered to involve an inventive step combined with one or more other such	when the document is			
"P" docume	ent published prior to the international filing date but later than trity date claimed	being obvious to a person skilled in th "&" document member of the same patent	e art			
	e actual completion of the international search	Date of mailing of the international s				
		1 6-10- 1997				
	ober 1997					
	mailing address of the ISA/ Patent Office	Authorized officer				
	S-102 42 STOCKHOLM	Marianne Bratsberg				
Facsimile 1	No. +46 8 666 02 86	Telephone No. +46 8 782 25 00				

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members			01/09/97	PCT/SI	E 97/01060		
 Patent document cited in search report		Publication date	Patent family member(s)	,	Publication date		
 SE	9303037-7	A	17/03/95	NONE			
 US	2706673	A	19/04/55	NONE		***************************************	
			•				
				•			
						•	